Note: This datasheet may be out of date

Please download the latest datasheet of DLM11SN900HY2#from the official website of Murata Manufacturing

Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=DLM11SN900HY2%23

### DLM11SN900HY2#

"#" indicates a package specification code.








< List of part numbers with package codes > DLM11SN900HY2B DLM11SN900HY2L



### Appearance & Shape





- Small size and tight dimensional tolerance Size:1.25x1.0x0.5mm
  Tolerance:+-0.1mm
- 2. High common mode impedance up to 90ohm (at 100MHz) is available.
- 3. DLM11S series enables noise suppression for differential signal line without distortion in high-speed signal transmission due to its line impedance matching.
- 4. High Cut-off Frequency.

(in mm)

# Applications

Other Usage For general



## Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	500
L	180mm Embossed Tape	4000

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=DLM11SN900HY2%23

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ DLM11SN900HY2\# from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ 

### DLM11SN900HY2#

"#" indicates a package specification code.

Note: This datasheet may be out of date



Shape	SMD
Size Code (in mm)	1210
Size Code (in inch)	0504
Length	1.25mm
Length Tolerance	±0.1mm
Width	1.0mm
Width Tolerance	±0.1mm
Thickness	0.5mm
Thickness Tolerance	±0.1mm
Common Mode Impedance (at 100MHz)	90Ω
Common Mode Impedance (at 100MHz) Tolerance	±25%
Rated Current	100mA
Rated Voltage	5Vdc
Withstanding Voltage	12.5Vdc
DC Resistance(max.)	1.38Ω
DC Resistance	1.1Ω±25%
Insulation Resistance(min.)	100ΜΩ

Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.004g
Number of Circuit	1
Operating Temperature Range(Self-temperature rise is included)	No

2 of 3

#### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/03/23


<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


https://www.murata.com/en-us/products/productdetail?partno=DLM11SN900HY2%23

### DLM11SN900HY2#


"#" indicates a package specification code.









Impedance-Frequency Characteristics







Differential Mode Transmission Characteristics (Typical Value)

**Equivalent Circuit** 

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/