



NOTE:

- 1. Rating: AC125V 5A/250V 3A
- 2. Operating force: 30±10gf
- 3. Mechanical Life: 1,000,000
- 3. Electrical Life: 6000-10,000

①	Aluminum rivet	—	1	Aluminum Alloy	—	—
⑩	Spindle	—	1	Brass	Plating Nicke	—
⑨	Roller	—	1	Brass	Plating Nicke	—
⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Lever	—	1	Stainless Steel	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE		 ELECTRONICS CO.,LTD		
DRAWN	J.X.Zhang	2014/7/21				
CHECKED				TITLE:	MICRO SWITCHS	
APPROVALS				PART NO.	K9-1910F	
TOLERANCES ARE	30~以下	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ:
	10~20	±0.25				
	5~10	±0.20	±2'	DRAWING NO.		SHEET 1 OF 1
	~ 5	±0.20				

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			