



一.电气性能:

- 1-1.额定电流: 3A AC DC.
- 1-2.接触电阻: $\leq 20m\Omega$
- 1-3.绝缘电阻: $\geq 1000M\Omega$ Min
- 1-4.耐 压: 500V AC/Minute

二.物理特性:

- 2-1.操作温度: $-40^{\circ}C \sim 105^{\circ}C$
- 2-2.焊接温度: $+220^{\circ}C$, 5s max

三.材质:

- 3-1.塑胶: PBT Black
- 3-2.插针: Brass/8-50U" nickel plated

topot 深圳市鑫冠辉电子有限公司

一般公差 COMMON TOLERANCES	图号 DWG. NAME	绘图 DRAWN	比例 SCALE
X	XGH-DWG-A1582	LXW	1:1
X.X	料号 PART NO.	审核 CHECKED	单位 UNIT
X.XX	JM1-1100-SBB-N0	LITYAN	MM
X.XXX	品名 TITLE	核准 APPROVED	版次 REV.
ANGLE	Mini Jump ² .54 2Pin 开口 黑色		A.0
	THIRD ANGLE PROJECTION:	日期 DATE	页次 SHEET
		2019-02-19	01
			图幅 SIZES
			A4

编号 DWG. NO.	标记 REV. LTR.	日期 DATE	变更内容 REVISION NOTES	签名 SIGN