


● 自锁式尼龙扎带 SELF-LOCKING CABLE TIES

- ◆ 材料: 采用UL认可之尼龙66料制成, 防火等级94V-2, 耐酸、耐蚀、绝缘性良好, 不易老化, 承受力强。
- ◆ 操作温度: -40℃ to 85℃
- ◆ 颜色: 标准颜色为白色(本色), 另有抗紫外线之黑色, 特殊颜色欢迎订做。
- ◆ Material: Nylon 66,94V-2
- ◆ Operating temperature: -40℃ to 85℃
- ◆ Color: Natural(or white,standard color),UV black and other colors are available as requestd.
- ◆ Certificate:UL . E220676



编号 Item Number	L(长)		W宽 (mm)	最大束线径 Max bundle dia(mm)	拉力 Tensile strength		包装 Packing
	INCH	mm			LBS	KGS	
HS-60A	2 3/8"	60	2.5	11	18	8	100PCS 或 1000PCS
HS-80A	3 3/16"	80	2.5	16	18	8	
HS-100A	4"	100	2.5	22	18	8	
HS-120A	4 3/4"	120	2.5	30	18	8	
HS-150A	6"	150	2.5	35	18	8	
HS-160A	6 1/4"	160	2.5	40	18	8	
HS-200A	8"	200	2.5	50	18	8	
HS-120B	4 3/4"	120	3.5	30	40	18	100PCS 或 500PCS
HS-150B	6"	150	3.5	35	40	18	
HS-180B	7"	180	3.5	42	40	18	
HS-200B	8"	200	3.5	50	40	18	
HS-250B	10"	250	3.5	65	40	18	
HS-280B	11"	280	3.5	70	40	18	
HS-300B	11 5/8"	300	3.5	80	40	18	
HS-370B	14 1/2"	370	3.5	102	40	18	
HS-120C	4 3/4"	120	4.5	24	50	22	
HS-150C	6"	150	4.5	35	50	22	
HS-190C	7 1/2"	190	4.5	46	50	22	





编号 Item Number	L(长)		W宽 (mm)	最大束线径 Max bundle dia(mm)	拉力 Tensile strength		包装 Packing
	INCH	mm			LBS	KGS	
HS-200C	8"	200	4.5	50	50	22	100PCS & 500PCS
HS-250C	10"	250	4.8	65	50	22	
HS-280C	11"	280	4.8	70	50	22	
HS-300C	11 5/8"	300	4.8	82	50	22	
HS-350C	13 3/4"	350	4.8	90	50	22	
HS-370C	14 1/2"	370	4.8	102	50	22	
HS-400C	15 3/4"	400	4.8	105	50	22	
HS-450C	17 3/4"	450	4.8	130	50	22	
HS-500C	19 11/16"	500	4.8	140	50	22	
HS-530C	20 4/5"	530	4.8	147	50	22	
HS-250DS	10"	250	6.8	65	90	40	100PCS
HS-300DS	11 5/8"	300	6.8	80	90	40	
HS-370DS	14 1/2"	370	6.8	102	90	40	
HS-150D	6"	150	7.6	33	120	55	
HS-200D	8"	200	7.6	50	120	55	
HS-250D	10"	250	7.6	63	120	55	
HS-300D	11 5/8"	300	7.6	82	120	55	
HS-350D	13 3/4"	350	7.6	90	120	55	
HS-370D	14 1/2"	370	7.6	102	120	55	
HS-400D	15 3/4"	400	7.6	105	120	55	
HS-450D	17 3/4"	450	7.6	118	120	55	
HS-500D	19 11/16"	500	7.6	150	120	55	
HS-550D	21 11/16"	550	7.6	160	120	55	
HS-430DL	17"	430	9	112	175	80	
HS-550DL	21 11/16"	550	9	160	175	80	
HS-650DL	25 9/16"	650	9	190	175	80	
HS-760DL	30"	760	9	225	175	80	
HS-810DL	32"	810	9	239	175	80	
HS-920DL	36 1/4"	920	9	265	175	80	
HS-1168DL	46"	1168	9	360	175	80	
HS-550FL	21 11/16"	550	12.7	160	250	114	