



NOTE:
 Rating: DC 12V 50mA
 Operating Force: 200 ± 100gf
 Lifetime: 100,000 Cycles

| PAPT NO | L |
|----------------|-----|
| SS-3336S-02-L1 | 2.0 |
| SS-3336S-02-L2 | 3.0 |
| SS-3336S-02-L3 | 4.0 |

| ITEM | PAPT NAMF | TER,NO | QTY | MATERIAL | FINISHING | REMARK |
|------|----------------|--------|-----|------------------|------------|--------|
| ⑤ | Terminal | — | 8 | Brass (0.30t) | ag Plated | — |
| ④ | Contact spring | — | 1 | Beryllium copper | — | — |
| ③ | Base | — | 1 | LCP | — | — |
| ② | Cover | — | 1 | SUS | Tin plated | — |
| ① | Keystake | — | 1 | PA46 | — | — |

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES | DSND | DATE | SCALE: N/A | MODEL TYPE: SLIDE SWITCH |
|------|-------------|------|---------|----------|------------------------|------|------|------------|-----------------------------|
| △X | | | | | ANGLAR ±5° | DWN | DATE | VIEW: | PART NO.: |
| △X | | | | | L ≤ 4 ±0.2 | CHKD | DATE | UNIT: mm | DWG NO.: |
| △X | | | | | 4 < L ≤ 16 ±0.3 | APPD | DATE | SIZE: A4 | SS-3336S-02-X |
| | | | | | 16 < L ≤ 63 ±0.4 | | | | WEIGHT |
| | | | | | L > 63 ±0.5 | | | | SHEET |
| | | | | | | | | | REVISION |
| | | | | | | | | | 1.0g |
| | | | | | | | | | 1/1 |
| | | | | | | | | | A0 |