



NOTE:  
 \*Products comply with ROHS requirements  
 \*Material:  
 1.Housing: PA66 UL94V-0  
 2.Terminal:Bronze(T=0.25mm)  
 3.Shell:SUS201(T=0.3mm)  
 \*Electrical Characteristics:  
 1.CONTACT RESISTANCE:30mΩ MAXIMUM  
 2.CONTACT CURRENT RATING:5A at VBUS and GND PIN  
 3.DIELECTRIC WITHSTANDING VOLTAGE:500 V R.M.S.  
 4.INSULATION RESISTANCE 1000 MEGOHMS MIN  
 5.OPERATING TEMPERATURE:-40°C ~ 85°C  
 \*Mechanical Characteristics:  
 1.MATING FORCE:3.57kg MAX  
 2.UNMATED FORCE:1.02kg MIN  
 3.DURABILITY:MANDATORY:5,000 CYCLES

Pin NUMBER	SIGNAL NAME	PRODUCT CHART DWG	TOLERANCE UNLESS OTHERWISE SPECIFIED
1	VBUS		X
2	D-		X
3	D+		X
4	GND		XX
5	GND_DRAIN		XXX

深圳市精拓金电子有限公司

单位	MM	制图	Z-Y-B	制料号
比例	1:1	审核		产品名称
日期	2015/04/24	核准		PRODUCT NO
DATE		APRD		角法
				版本
				VER
				AD

MAPX	MODIFICATION	DATE

