



PCB Layout (Pattern side) [®] Circuit Diagram

PART NO	H	L	F
A	4.3	2.80	$\phi 3.40$
C	5	3.50	$\phi 3.40$
D	5.5	4.00	$\phi 3.40$
E	6	4.50	$\phi 3.40$
G	7	5.50	$\phi 3.20$
I	8	6.50	$\phi 3.20$
K	9	7.50	$\phi 3.20$
L	9.5	8.00	$\phi 3.20$

NO.2	
PART NO	vigor
1	90 ± 30
2	130 ± 30
3	180 ± 30
4	250 ± 30
5	350 ± 50

NO.3	
PART NO	MATERIAL/ QTY
S	SUS/1PC
C	C5210/1PC
D	SUS/2PCS
F	C5210/2PCS

NO.4-NO.5	
PART NO	NOTE
01~99	SERIAL NUMBER

⑥	Trestle	—	1	SPCC	Plating Nickel	—
⑤	Terminal	—	2	Brass($\phi 3.0$)	Plating silver	—
④	Contact	—	1	F.Ag/SUS	Plating silver	—
③	Base	—	1	Nylon	Black	—
②	Cover	—	1	SPCC	Plating Nickel	—
①	Keystroke	—	1	Nylon	Black	—

APPROVALS		DATE	
DRAWN	J.X.Zhang	DATE	2013/5/30

CHECKED		TITLE:	
APPROVALS		TACT SWITCHS	
TOLERANCES ARE		PART NO. K2-1102BG-□□□□W-□□	
30~12.5	± 0.30	UNIT: mm	SCALE: 1:1
10~30	± 0.20	DRAWING NO.	PROJ:
5~10	± 0.15		SHEET 1 OF 1
~5	± 0.10		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	B		NEW			
	A					