



电镀: 镀铜底80U" 镀镍120U"  
 ▲"为重点检验尺寸。

MAPX	MODIFICATION	DATE

NOTES:  
 Housing: Thermoplastics  
 Contact: Copper Alloy  
 Shell: Copper Alloy/Steel  
 Voltage Current Rating: 1.5 AMP. 30V AC  
 Insulation Resistance: 1000MΩ Min.  
 Contact Resistance: 30 MΩ Max.  
 Dielectric Withstanding Voltage: 500W AC  
 Temperature Range: -55° C to +85° C  
 Insulator color: Black/White  
 Plastic material: PBT/LCP  
 Shell finish: Nickel plated/Tin-Lead plated  
 Contact finish:  
 01: Selective Gold Flash  
 02: Selective Gold 3U"  
 03: Selective Gold 5U"  
 04: Selective Gold 15U"  
 05: Selective Gold 30U"

# 深圳市精拓金电子有限公司

公差一览表		单位		MM	
TOLERANCE UNLESS OTHERWISE SPECIFIED	公差	UNITS	DRAWING	PRODUCT PART NO.	制图料号
X	±0.15	X	45°		
X	±0.10	X	±2°		
.XX	±0.05	.XX	±1°		
.XXX	±0.03	.XXX	±0.5°		
DATE	2012.04.18	SCALE	1:1	DATE	2012.04.18
APRD	核准	CHKD	审核	APRD	核准
Z-Y-B		PRODUCT NO.	产品名称	VIEW	角注
			USB AM前壳	VER	版本
					A0

1 2 3 4 7 8 9 10

由 Autodesk 教育版产品制作