



- NOTE:
- 1.Rating: 24V 25mA AC
  - 2.Insulation Resistance:≥100 MΩ
  - 3.Withstand voltage:AC 500V 1Minute
  - 4.Operating Force Range: 400gf Max
  - 5.Mechanical Life:3,000 Cycles
  - 6.Operating Temperature range -20~+70°C
  - 7.Ambient Humidity used: ≤85%RH

Position(位数)	2P	3P	4P	5P	6P	7P	8P	9P	10P	12P
DIM.A(长度)	6.54	9.08	11.62	14.16	16.70	19.24	21.78	24.32	26.86	31.94
DIM.B(长度)	2.54	5.08	7.62	10.16	12.70	15.24	17.78	20.32	22.86	27.94
PART NO. 盖子/红色(R)	短柄(S)	DS-02RS	DS-03RS	DS-04RS	DS-05RS	DS-06RS	DS-07RS	DS-08RS	DS-09RS	DS-10RS
PART NO. 盖了/红色(R)	短柄(S)	DS-02BP	DS-03BP	DS-04BP	DS-05BP	DS-06BP	DS-07BP	DS-08BP	DS-09BP	DS-10BP
	短柄(S)	DS-02BS	DS-03BS	DS-04BS	DS-05BS	DS-06BS	DS-07BS	DS-08BS	DS-09BS	DS-10BS
										DS-12BS

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑤	Gum Water	—	—	—	Black	—
④	Terminal	—	—	Phosphor bronze	Au Plating	—
③	Base	—	1	PBT	Black	—
②	Cover	—	1	PBT	Red/Blue	—
①	Keystroke	—	1	PBT	White	—

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
<p>DRAWN J.X.Zhang 2013/11/8</p> <p>CHECKED</p> <p>APPROVALS</p> <p>TOLERANCES ARE 30%以上 ±0.30 10~30 ±0.20 5~10 ±0.15 ~5 ±0.10</p> <p>ANGLE ±2°</p> <p>UNIT: mm</p> <p>SCALE: 1:1</p> <p>DRAWING NO.</p> <p>SHEET 1 OF 1</p>						
<p>APPROVALS DATE</p> <p>TERMINALS</p> <p>DATE</p> <p>TITLE: MULTIFUNCTIONAL SWITCHES</p> <p>PART NO. DS-□□□□</p> <p>PROJ. SHEET</p>						
<p>ELECTRONICS CO.,LTD</p>						