








REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE



Note:

1.Material:

- 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: copper alloy,t=0.15mm
- 1.3 Shell: copper alloy,t=0.30mm

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 50 mW Max.
- 2.4 Insulation resistance: 100 MW Min.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min.0.81~2.05 Kgf Min.after 10000 insertion/extraction cycles
- 2.7 Temperature range: -30°C~80°C

A 01 S B X X X X X X 1-067

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬

- ① 产品代号 A:成品
- ② 产品系列 01:micro usb 5pin
- ③ 产品类别 S:母座
- ④ 产品类型 B:B TYPE
- ⑤ 外壳材质 1:C2880R-H
- ⑥ 外壳电镀 0:素材;1: Ni100u";2:雾Sn100u";3:Ni+Au1u" (圆);4:全Au1u"
- ⑦ 端子材质 4:05191R-EH 2:C2880R-EH
- ⑧ 端子电镀 0:素材;1:全Au1u";2:全Au1.5u";3:全Au1u";4:全Au0.5u";5:全Au1u";6:全Au0.5u";7:雾Sn100u";8:雾Sn100u";9:雾Sn100u";10:雾Sn100u"
- ⑨ 主体材质 1:LDP
- ⑩ 主体颜色 B:黑色 W:白色
- ⑪ 包装方式 1:吸塑管;2:卷带;4:pe袋
- ⑫ 下板类型 1:DIP
- ⑬ 细节流水 067:MICRO USB SS B TYPE 四脚全插(牛角型)短针

PART NO: A01SBXXXXXXX1-067		MATERIAL: SEE NOTE	深圳市金航标电子有限公司	WWW.BDS666.COM
MODEL NO: XX		FINSH: SEE NOTE	KH-MICRO5P-N	0755-83044319
UNIT: MM	SIZE: A4	COLOR: SEE NOTE	TITLE: MICRO USB SS B TYPE 四脚全插(牛角型)短针	
TOLERANCE UNSPECIFIED		DR: 夏友红	DWG NO: A067	
.x	0.25	CHK:	REV: A	
.xx	0.15	APP:	SCALE: 5:1	
.xxx	0.10		DATE: 2012.05.02	
Ang.	2°			