


SPECIFICATIONS:

Current Rating : 3AMP
 Insulator Resistance: 1000Megohms min
 Voltage Rating: AC 500V
 Operating Temperature: -40° ~+85°
 Max Processing Temp: 220° for 3~5 seconds
 Contact Material: Aolly
 Insulator Material: PA6T Black
 Plating: G/F Plated over Nickel



Contacts Per Row	Dimensions		Contacts Per Row	Dimensions	
	A	B		A	B
1*2pin	5.08	2.54	1*2pin	53.34	50.80
1*3pin	7.62	5.08	1*3pin	55.88	53.34
1*4pin	10.16	7.62	1*4pin	58.42	55.88
1*5pin	12.70	10.16	1*5pin	60.96	58.42
1*6pin	15.24	12.70	1*6pin	63.50	60.96
1*7pin	17.78	15.24	1*7pin	66.04	63.50
1*8pin	20.32	17.78	1*8pin	68.58	66.04
1*9pin	22.86	20.32	1*9pin	71.12	68.58
1*10pin	25.40	22.86	1*10pin	73.66	71.12
1*11pin	27.94	25.40	1*11pin	76.20	73.66
1*12pin	30.48	27.94	1*12pin	78.74	76.20
1*13pin	33.02	30.48	1*13pin	81.28	78.74
1*14pin	35.56	33.02	1*14pin	83.82	81.28
1*15pin	38.10	35.56	1*15pin	86.36	83.82
1*16pin	40.64	38.10	1*16pin	88.90	86.36
1*17pin	43.18	40.64	1*17pin	91.44	88.90
1*18pin	45.72	43.18	1*18pin	93.98	91.44
1*19pin	48.26	45.72	1*19pin	96.52	93.98
1*20pin	50.80	48.26	1*20pin	99.06	96.52

P.C.B. LAYOUT

toppt 深圳市鑫冠辉电子有限公司

一般公差 COMMON TOLERANCES	图号 DWG. NAME	绘图 FLOT	比例 SCALE
X	XGH-DWG-A115	LXW	1:1
X.X	料号 PART NO.	审核 CHECKED	单位 UNIT
X.XX	PHI-E1XX-SRB-60	LITYAN	MM
X.XXX	品名 TITLE	核准 APPROVED	版次 REV.
ANGLE	排针2.54 1*NP 180度 PC3.0mm L=11.5mm	日期 DATE	页次 SHEET
	THIRD ANGLE PROJECTION:	2019-02-18	01
			图幅 MMS
			A4

编号 DWG. NO.	标记 REV. LTR.	日期 DATE	变更内容 REVISION NOTES	签名 SIGN