



4. CONTACT FINISH:
- 01: Selective Gold Flash
  - 02: Selective Gold 3U"
  - 03: Selective Gold 5U"
  - 04: Selective Gold 15U"
  - 05: Selective Gold 30U"
3. ENVIRONMENTAL:
- OPERATING TEMPERATURE: -55°C +85°C

- NOTES:
- 1. HOUSING: SEE NOTES, TERMINAL: SEE NOTES, SHELL: SEE NOTES.
  - 2. MECHANICAL CHARACTERISTIC:
    - INSERTION FORCE: 35N(3.57KG) MAX
    - EXTRACTION FORCE: 10~35N(1.02~3.57KG) MIN
    - DURABILITY: 1500 CYCLES EXTRACTION FORCE: 10~35N 5000 CYCLES MIN
    - 5000 CYCLES EXTRACTION FORCE: 3~35N
  - 1. ELECTRICAL CHARACTERISTIC:
    - CONTACT RESISTANCE: 30MΩ MAX
    - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1MIN
    - INSULATION RESISTANCE: 1000MΩ MIN

MAPX	MODIFICATION	DATE
------	--------------	------

# 深圳市精拓金电子有限公司

产品图 PRODUCT CHART DWG 公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS MM		制图 DRAWING Z-Y-B		制图料号 PRODUCT PART NO. JTJ-USB-10.6-001	
X	±0.15	X	±5°				
X	±0.10	X	±2°				
XX	±0.05	XX	±1°				
XXX	±0.03	XXX	±0.5°				
DATE	2012.09.24	审核	核准			角法	版本
		APPD				VIEW	VER
							AD

