




[PAGE BACK](#) [CLOSE](#)

Product Name Multilayer Inductor for Ultra High
Series MLK Series
Type 1005 Type
Part Number MLK1005S5N6DT000

Product Lifecycle Stage PROD



Specification

Mounting Method Flag	Yes	
Processing	MULTI-LAYER	
Shape	SMD	
Size Code	1005	
Body Length(L)	Nom	1 m m
Body Breadth(W)	Nom	0.5 m m
Body Height(T)	Nom	0.5 m m
Rated Inductance	Nom	5.6 n H
Inductance Tolerance (Value)	Min	-0.5 n H
	Max	0.5 n H
Test Frequency of Inductance	Nom	100 M Hz
	Min	7
Q	Typ	9
	Nom	100 M Hz
Test Frequency of Q	Min	5.7 G Hz
	Typ	6.7 G Hz
DC Resistance	Max	0.3 Ohm
	Nom	0.15 Ohm
Rated Current	Max	400 m A
IDC1 (Inductance Change)	Max	400 m A
IDC2 (Temperature Rise)	Max	400 m A
Temperature Rise	Max	20 Cel
Terminal Material	Ag(100%)/Sn plating	
Polarity Marking	No	
Magnetic Shielding	No	
Soldering Method	Reflow,Iron Soldering	
Measuring Equipment(L, Q, Rdc)	L,Q:HP4291A+16193A, Rdc:YOKOGAWA TYPE7561	
Category Temperature Range	Min	-55 Cel
	Max	125 Cel
Storage Temperature Range	Min	-55 Cel

Summary/Applications/Feature

Summary	Small size High-Q RF coil for high frequency circuit of mobile application. Pb free and correspond to Pb free soldering.
Applications	Cellular,VCO module,PA module,Bluetooth,other high frequency circuit for mobile applications
Feature	Small size High-Q RF coil for high frequency circuit of mobile application. High Self Resonance Frequency (SRF). No polarity. Lead free, lead free soldering, and RoHS compliant

Packaging

Packing	Punched (Paper)Taping [180mm Reel]	
Minimum Package Qty	Nom	10000 Pcs
Minimum Order Qty	Nom	10000 Pcs

[Details](#)

	Max	125 Cel
Weight	Nom	0.001 g

☛ [**Caution**]

Specifications which provide more details for the proper and safe use of the described product are available upon request.

☛ [**Notice of Revision and Improve**]

All specifications are subject to change without notice.

[PAGE TOP](#) 

Copyright(c) 1996-2008 All rights reserved.